

## EP243TDE

Article code: 991012403



**Europower open generating sets with Kubota water-cooled diesel engines, 3000rpm, 50Hz, 4 stroke**

### **Generator:**

kVA max.:	24
kVA cont.:	23
Amps cont.:	35A @ 1~230V    27A @ 3~400V
Dimensions l x w x h:	150x74x86cm
Weight incl. oil + coolant, excl. fuel:	360kg

### **Engine:**

<b>Brand/Type:</b>	<b>Kubota V1505</b>
HP:	35.3
Power:	21.6kW (3000rpm), 4-cylinder Diesel, Water-cooled
Displacement:	1498cm <sup>3</sup>
Consumption @75% load:	6.5 litres/hour
Tank:	65 litres
Autonomy @75% load:	10.0 hours
Noise level:	83dB(A)@7m (*)
EU Emission norm:	IIIA
Battery voltage:	12V

### **Alternator:**

<b>Brand/Type</b>	<b>Mecc Alte ECP28-2L/2 - brushless</b>
Nominal voltage:	3~400V and 1~230V
Frequency:	50Hz
Protection degree:	IP23

Generators with \* cannot be used outdoors in the EU. For applications of generating sets indoors, or if you want to integrate these generators in vehicles, please contact us.

At present all EU portable generators in the power range from 18 to 560kVA are required to meet Stage IIIA regulations. A portable generator is either a rental set or a unit that is moved more than twice a year. The EU does not regulate emissions from stationary diesel generators used for prime power, peak shaving or emergency standby power.

**VERSION:**

- 1 socket 230V - 16A + 1 socket CEE 230V - 32A + 1 socket CEE 400V - 32A 5 p.
- Automatic voltage regulator
- Earth leakage protection 30mA with earth pin and 4m earth cable
- Electric start, maintenance free battery included
- Emergency stop
- Fuel pump 12V
- High temperature security
- Hour counter
- Low oil pressure guard
- Magneto-Stop
- Mechanical fuel level meter
- Oil drain pump
- Thermal magnetic breaker
- Voltmeter

www.EUROPOWERGenerators.com

The Kubota logo is written in a stylized, teal-colored font.

Your **EUROPOWER** dealer